

# Technical data sheet

Socket 33°, Connect 45, protective contact, double

Item number: 6120489



Protective contact socket double 33°, with increased touch protection, with screwless terminals, 2-pin, 16 A, 250 V~, with connection terminals to IEC 60884-1.

For installation in Rapid 45 ducts, device installation ducts, installation columns, underfloor systems and Deskboxes.



PC Polycarbonate

## Master data

|                                   |                                |
|-----------------------------------|--------------------------------|
| Item number                       | 6120489                        |
| Description 1                     | Socket 33°, double             |
| Description 2                     | protective contact, Connect 45 |
| Manufacturer                      | OBO                            |
| Dimension                         | 250V, 10/16A                   |
| Colour                            | Signal red; RAL 3001           |
| Material                          | Polycarbonate                  |
| Smallest sales unit               | 1                              |
| Unit of quantity                  | Piece                          |
| Weight                            | 8.5 kg                         |
| Weight unit                       | kg/100 pc.                     |
| CO Footprint (GWP) Cradle-to-Gate | 0,2945 kg COe / 1 Piece        |

# Technical data sheet

Socket 33°, Connect 45, protective contact, double

Item number: 6120489



## Dimensions

|        |       |
|--------|-------|
| Width  | 90 mm |
| Height | 45 mm |



## Technical data

|  |                              |
|--|------------------------------|
| Cover  | Central plate                |
| Closable   | no                           |
| Connection type                                  | Screwless terminal           |
| Number of units                                  | 2                            |
| Number of modules (for modular construction)     | 0                            |
| Number of switchable sockets                     | 0                            |
| Number of poles                                  | 2                            |
| Printed label/coding                             | Without printing             |
| Version for                                      | double 33°                   |
| Surface version                                  | Matt                         |
| Version for                                      | SCHUKO                       |
| Ejection mechanism                               | no                           |
| Fastening type                                   | Lock                         |
| Labelling panel                                  | no                           |
| Operating temperature, max.                      | 40 °C                        |
| Operating temperature, min.                      | -5 °C                        |
| increased touch protection                       | yes                          |
| Error current protection                         | no                           |
| For more difficult conditions (according to VDE) | no                           |
| Halogen-free                                     | yes                          |
| Insulated installation                           | no                           |
| Hinged cover                                     | no                           |
| Coding   | no                           |
| Warning light                                    | no                           |
| With on/off switch                               | no                           |
| With fine-wire fuse                              | no                           |
| With functional lighting                         | no                           |
| With orientation lighting                        | no                           |
| Mounting type                                    | Device installation duct     |
| Nominal voltage                                  | 250 V                        |
| Nominal current                                  | 16 A                         |
| Protection rating                                | Other                        |
| Special power supply                             | Without special power supply |
| Socket version                                   | Protective contact           |
| Socket angle                                     | 33°                          |
| Depth  | 40 mm                        |
| Transparent                                      | no                           |
| Rotated central insert                           | yes                          |
| Approvals  | VDE                          |
| Surge protection                                 | no                           |